










































Products	Ref	Price	Specifications
<b>HPS SYSTEMS</b>			
	EM		<b>Power supply 4,5V (batteries) - single point</b>
	MEMOLUB® EM EX II (ATEX approval)	6130	120cc - 10bar
	ONE		<b>Power supply 4,5V (batteries) - single point</b>
	MEMOLUB® ONE EX II (ATEX approval)	6110	240cc - 10bar
	Starter Pack MEMOLUB® ONE EX II with Memomulti 2 (ATEX approval)	6115	Starter Pack 240cc - 10bar: MEMOLUB® ONE filled with Memomulti 2, 4 MEMOS, installation kit, batteries
	Starter Pack MEMOLUB® ONE EX II w/out grease (ATEX approval)	6120	Starter Pack 240cc - 10bar: MEMOLUB® ONE , 4 MEMOS, installation kit, batteries
	HPS		<b>Battery power supply 4,5V - multipoints</b>
	MEMOLUB® HPS 120cc EX II (ATEX approval)	6000	120cc - 25bar
	MEMOLUB® HPS 240cc EX II (ATEX approval)	6001	240cc - 25bar
	MEMOLUB® HPS 480cc EX II (ATEX approval)	6002	480cc - 25bar
	EPS		<b>External power supply 24V - multipoints</b>
	MEMOLUB® EPS 24V 120cc	6020	120cc - 25bar
	MEMOLUB® EPS 24V 120cc	6021	240cc - 25bar
	MEMOLUB® EPS 24V 480cc	6022	480cc - 25bar
	PLCD		<b>PLC driven power supply 24V - multipoints</b>
	MEMOLUB® PLCD 120cc (24V)	6010	120cc - 25bar
	MEMOLUB® PLCD 240cc (24V)	6011	240cc - 25bar
	MEMOLUB® PLCD 480cc (24V)	6012	480cc - 25bar
<b>HPS Accessories</b>			
		Ref	Price
<b>Spares Parts</b>			
	HPS Transparent housing		
	Transparent housing PA12 120cc	2208	Transparent housing in polyamide for UV and aggressive environments. 120cc, 240cc
	Transparent housing PA12 240cc	2209	
	Transparent housing 480cc	2210	Transparent housing 480cc
	HPS Locking ring		
	Locking ring	2203	
	HPS Compression plate		
	Compression plate	2204	
	HPS Battery seal		
	Battery seal	2206	
	Complete HPS housing kit		
	120cc STANDARD kit PA12	1204	Transparent housing, locking ring, compression plate, spring (120cc, 240cc and 480cc)
	240cc MEGA kit PA12	1205	
	480cc GIGA kit	1203	
	Battery pack		
	Battery pack	5001	3*1,5V Alkaline batteries
	Volumetric rings for BPS/EPS/PLCD		
	Stroke washer (MOQ : 250)	2401	Rings to adjust volume per stroke
	Stroke washer clip (MOQ : 40)	2402	
	Memo screw		
	Memo screw	1301	Memo screw
	Memo BPS/EPS kit		
	Memo BPS/EPS/PLCD kit	1101	Memo screw, Memo ring holder, Frequency rings
	Memo EM/ONE kit		
	Memo screw	2801	4 screwable parts to set frequency
	Screw connection EPS		
	Kit screw connector EPS	1550	For EPS model only

HPS Accessories		Ref	Price	Specifications
<b>Installation</b>				
	Extension kit for EM/ONE			Kit for remote installation
	Extension kit for EM/ONE	1108		Mounting Bracket, Fittings for fixation for tube 6mm, 2 meters of Rilsan tube 4x6mm
	Extension kit for BPS/EPS/PLCD			Kit for remote installation
	Extension kit for BPS/EPS/PLCD	1508		Mounting bracket, adaptor G1/4 for tube 8mm
	Distribution			Multi points installation
	DB4	2701		
	DB6	2702		
	DB8	2703		
	Kit Distrilube DB2 (Kit DB4 + 2 Y fittings)	1509		
	Kit Distrilube DB4	1505		Installation kit for DB, distributor block 2-4-6 or 8 outlets, bracket & 2 push-in G1/8 per outlet
	Kit Distrilube DB6	1506		
	Kit Distrilube DB8	1507		
<b>Lubrication Control</b>				
	Proximity Switch	2552		Magnetic sensor for lubrication feedback
	Proximity Switch Cable 60cm	2553		Cable to install proximity switch on DB
	Kit Distrilube DB4 with a Proximity Switch	1544		Proximity switch already installed on a kit distrilube
	Kit Distrilube DB6 with a Proximity Switch	1546		Proximity switch already installed on a kit distrilube
	Kit Distrilube DB8 with a Proximity Switch	1548		Proximity switch already installed on a kit distrilube
	Bridging Element			
	Bridging Element	2705		Blocks 1 outlet and double the output of another outlet
	Installation kit DB			
	Installation kit DB	1520		Installation kit for Block Distributor
	Protection Cover			
	Protection Cover 120-240cc	2211		Protection against hostile atmospheres
	Protection Cover 480cc	2212		
	Silent Block M6			Mitigate vibrations to protect Memolub
	Silent Block M6	3053		Silent Block M6
<b>Oil applications</b>				
	Natural brush			Animal-origin made
	Natural brush 15mm	2810		Natural brush + adaptor 15mm - 30mm - 45mm
	Natural brush 30mm	2811		
	Natural brush 45mm	2812		
	Nylon brush			Nylon made
	Nylon brush flat 30x4mm	2813		Nylon bijur brush flat + adaptor
	Nylon brush circular - Ø16mm	2814		Nylon bijur brush circular + adaptor
	Inox brush			
	Inox brush 16mm	2815		Inox brush 16mm + adaptor
	Check valve DB			
	Check valve DB	2800		For using into DB, it prevents oil leaks
	Check valve Memo HPS/ Brush			
	Check valve Memo HPS	2806		Put into the Memo BPS/EPS/Brush, it prevents oil leaks
	TOM			Offset oil leaks up to 1 liter
	TOM 500ml	2990		Oil reservoir 500ml
	TOM 1000ml	2991		Oil reservoir 1000ml
<b>Alternative lubricant dispensers</b>				
	Rail crane			Precise & accurate rail lubrication
	Rail crane	3026		Reduce rails deterioration
	Spray nozzle			Lubricates over a large surface
	Spray nozzle	2700		Spray nozzle
	Felt Pinion			Ideal to lubricate racks and chains
	Felt Pinion	od*		on demand

\*on demand

HPS Accessories		Ref	Price	Specifications
<b>Brackets</b>				
	Memo Bracket			
	Memo Bracket	2720		Mounting Bracket to install HPS products
	DB Stainless Bracket			
	DB Stainless Bracket	2760		Mounting Bracket to install distributor blocks
	Brush Bracket			
	Brush Bracket	2719		Bracket to install brushes
<b>Tubes</b>				
	Rilsan Tube			Temperature range: [-40°C ; +80°C]
	Rilsan PA12 Tube 6/8mm	2723		Polyamide/Nylon tube 6/8mm
	Rilsan PA12 Tube 4/6mm	2728		Polyamide/Nylon tube 4/6mm
	Consolidated Rilsan Tube			Temperature range: [-40°C ; +70°C]
	Consolidated Rilsan Tube 6/8mm	2746		Consolidated Polyamide/Nylon tube 6/8mm
	Consolidated Rilsan Tube 4/6mm	2747		Consolidated Polyamide/Nylon tube 4/6mm
	PTFE Tube			Temperature range: [-200°C ; +120°C]
	PTFE Tube 6/8mm	2748		PTFE Tube 6/8mm
	PTFE Tube 4/6mm	2749		PTFE Tube 4/6mm
<b>Fittings and adaptors</b>				
	Push-in Connections			Max temperature: +70°C
	Push-in connections G1/8 - Ø8	2724		Push-in connections G1/8 - Ø8
	Push-in connections G1/8 - Ø6	2729		Push-in connections G1/8 - Ø6
	Elbow Fittings			Max temperature: +70°C
	Elbow fitting G1/8 - Ø8	2711		Elbow fitting G1/8 - Ø8
	Elbow fitting G1/8 - Ø6	2712		Elbow fitting G1/8 - Ø6
	Y Fittings			Max temperature: +70°C
	Y fitting - Ø6	2744		Y fitting - Ø6
	Y fitting - Ø8	2745		Y fitting - Ø8
	Olive Fittings			Max temperature: +180°C
	Olive fitting G1/8 - Ø6	2765		Olive fitting G1/8 - Ø6
	Olive fitting G1/8 - Ø8	2766		Olive fitting G1/8 - Ø8
	Olive fitting G1/4 - Ø6	2767		Olive fitting G1/4 - Ø6
	Olive fitting G1/4 - Ø8	2768		Olive fitting G1/4 - Ø8
	Olive Elbow Fittings			Max temperature: +180°C
	Olive elbow fitting G1/8 - Ø6	2769		Olive elbow fitting G1/8 - Ø6
	Olive elbow fitting G1/8 - Ø8	2772		Olive elbow fitting G1/8 - Ø8
	Olive elbow fitting G1/4 - Ø6	2773		Olive elbow fitting G1/4 - Ø6
	Olive elbow fitting G1/4 - Ø8	2775		Olive elbow fitting G1/4 - Ø8
	Adaptors M-F			Max temperature: +70°C
	Adaptor M-F M6x100 - G1/8	2732		Adaptor M-F M6x100 - G1/8
	Adaptor M-F M8x100 - G1/8	2733		Adaptor M-F M8x100 - G1/8
	Adaptor M-F M10x100 - G1/8	2735		Adaptor M-F M10x100 - G1/8
	Adaptor M-F M10x125 - G1/8	2736		Adaptor M-F M10x125 - G1/8
	Adaptor M-F M10x150 - G1/8	2737		Adaptor M-F M10x150 - G1/8
	Adaptor M-F M12x125 - G1/8	2738		Adaptor M-F M12x125 - G1/8
	Adaptor M-F M12x150 - G1/8	2739		Adaptor M-F M12x150 - G1/8

DS Accessories		Ref	Price	Specifications
<b>Basic DS system spare parts</b>				
	DS Pump			
	DS 18 Pump	1800		DS Pump for 18kg pails
	DS 50 Pump	1801		DS Pump for 50kg pails
	Electronic Box			Settings controller and power transformer
	Electronic Box DS 230V	2870		Electronic Box DS 230V
	Electronic Box DS 24V	2875		Electronic Box DS 24V
	Check Function Control			
	Check Function Control	2876		5m control cable to manually check function
	DS Cover Lid			Lid to lock DS pump on its pail
	DS Cover Lid Ø320mm Lid 18-30kg	2728		DS Cover Lid Ø320mm Lid 18-30kg
	Custom DS Cover Lid	od*		Custom DS Cover Lid
	DS Follower Plate			Consolidated Polyamide/Nylon tube 6/8mm
	DS Follower Plate 18-30kg (Castrol version)	2865		Consolidated Polyamide/Nylon tube 4/6mm
	DS Follower Plate 18-30kg (Other lubricant)	1806		Temperature range: [-200°C ; +120°C]
	DS Installation Kit			
	DS18-50 Installation kit	1810		Installation Kit for DS18 and DS50
<b>Distributor Blocks and Accessories</b>				
	Distributor Blocks			Volume per outlet: 0.1cc
	DS Block 2 Outlets	2360		DS Distributor Block 2,4,6,8,10,12,14,16,18 or 20 outlets
	DS Block 4 Outlets	2361		
	DS Block 6 Outlets	2362		
	DS Block 8 Outlets	2363		
	DS Block 10 Outlets	2634		
	DS Block 12 Outlets	2885		
	DS Block 14 Outlets	2886		
	DS Block 16 Outlets	2887		
	DS Block 18 Outlets	2888		
	DS Block 20 Outlets	2889		
	Proximity Switch			
	DS Proximity Switch	2892		DS Proximity Switch
<b>Tubes and fittings</b>				
	DS Tube Rilsan Air			
	DS Tube Rilsan blue/air 6X8mm	2791		Air tube between Electronic Box and DS Pump
	DS Tube Rilsan blue/air 4x6mm	2792		
	DS Tube High Pressure			up to 350bar
	DS Tube high pressure 350bar - 8x14.3mm	2793		Tube between DS Pump and Distributor Block
	DS Fitting High Pressure			Fittings between DS Pump and Distributor Block
	DS Fitting High Pressure female 8x14.3mm	2872		Female
	DS Fitting High Pressure male 8x14.3mm	2873		Male
	Rilsan Tube			
	Tube 6/8mm (roll of 100m)	2723		Tube between DS Distributor Block and lubrication points
	Push-in			Max temperature: +70°C
	Push-in 1/8 T8/6mm	2724		Push-in 1/8 T8/6mm
	Elbow Fitting			Max temperature: +70°C
	Elbow Fitting D8 1/8	2711		Elbow Fitting D8 1/8

\* on demand